


# **HOTSOAK 73**

## HOTSOAK SERIES MODEL # AI18AIR7242HS




















Rough-In Plumbing

### SPECIFICATIONS:

#### **GENERAL SPECIFICATIONS:**

72" x 42" x 24" **Tub Size** 

189 cm x 107 cm x 56 cm

**Bathing Well** 49" long

24 1/2" wide 22" interior depth

188 lbs. / 85.5 kg Shipping Weight **Tub Weight Filled** 1359 lbs. / 618 kg **Tub Weight Only** 138 lbs. / 63 ka Gallons to Overflow 163 gal. / 618 L

#### **ELECTRICAL SPECIFICATIONS:**

1/15 HP; 1.3 AMP; 110V Pump 1.5 kW; 12.5 AMP; 110V Heater Requirements 20 AMP; 110V, separate circuit required protected w/ Class A GFCI

### STANDARD EQUIPMENT:

#### **Aquatic Quality Features:**

- 1.5 kW Inline Maintenance Heater
- Run-Dry Pump with 20-Minute Timer
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Operation
- Slip Resistant Floor
- Extra Deep and Long Bathing Well
- Pre-leveled ABS Support Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

**UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty** 

# **OPTIONAL EQUIPMENT:**

- Chromatherapy LED Lighting\*
- Comfort Pillow Oval or Rectangle
- **Bolt-On Grab Bars** 
  - White, Biscuit, Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Lift & Turn Waste and Overflow
  - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
  - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Integral Tiling Flange (Customer must specify which side(s) should receive flange)
- **Premium Colors**

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

\*This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

117

Fax-On-Demand Document #1248



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub: Aquatic Industries, Inc. assumes no responsibility for preparatory work. www.aguaticwhirlpools.com 800,555,5324

August 2008